



CAMARA

Image Sensor 1/4" Progressive Scan CMOS Sensor

Resolution 1.0 Megapixel (1280 x 720)

Lens F: 2.8, f: 3.85 mm

Viewing Angle FOV = 64°

Digital Zoom 4x Digital

VIDEO/IMAGEN

Video Streaming Controllable Frame Rate

Image Settings Rotation: Mirror, Flip

Configurable Brightness, Contrast, and Saturation

Overlay Capabilities: Time, Date, and Text

AUDIO

Audio Communication 1-Way

Audio Input Built-in Microphone

ALARM AND EVENT MANAGEMENT

Notification E-Mail

Triggering Event Motion/Sound Detection

NETWORK

Standards and Protocols Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP,DNS,

UPnP, HTTP and UDP

Security Multiple Password-Protected User Levels

WIRELESS

Wireless Data Rates IEEE 802.11 b/g/n, Up to 300Mbps

Frequency 2.4GHz - 2.4835GHz

Wireless Transmit Power <20dBm (EIRP)

Wireless Encryption WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

INTERFACES

Network Interface RJ-45 for Ethernet 10/100 Base-T

Power Connector DC Power Jack

Button Reset/WPS Push Button

SURVEILLANCE MANAGEMENT

Free Management Software Viewing and Recording up to 36 Cameras

MINIMUM SYSTEM REQUIREMENTS

Supported OS Windows 10/8/7/Vista/XP

OS X or higher

iOS 7.0 or higher

Android 3.0 or higher

Supported Browser Mozilla Firefox 4.0, Opera 12, Safari 4.0, IE 7.0 or higher

GENERAL

External Power Supply 9V DC, Max 5.4W

Certification RoHS, FCC, CE

Package Contents NC250

Power Adapter

Extension Cable

RJ-45 Ethernet Cable

Quick Installation Guide

Environment Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C ~70°C (-40°F ~158°F)

Operating Humidity: 10%~90% Non-Condensing

Storage Humidity: 5%~90% Non-Condensing

Dimensions(H X W X D) 5.4 x 3.0 x 2.7 in. (137 x 76 x 69 mm)

Packaging Dimensions 5.0 x 3.1 x 8.8 in. (128 x 79.5 x 223mm)